

Two Lines Professional WIFI IP Phone **WS320**



WS320 is a small-screen-based wireless IP phone in SayHi IP phone, it has fashion and technological appearance, excellent voice quality, and powerful features, and it is a new generation of intelligent phones to replace of the traditional desktop office terminals, It accomplished the powerful telephony features by cooperating with the communications platform,. such as the call transfer, hotline, three-party conference calling, speed dial, voice mail, Do Not Disturb, etc.

Key Features

- ▶ Wireless connect to the network
- ▶ HD Voice: HD Codec, HD Speaker, HD Handset
- ▶ Multi-Language :Chinese,English,French,Russian,etc.
- ▶ Excellent adjustable bracket and wall-mountable
- ▶ Two SIP accounts and support three-way conference, SMS
- ▶ 2xLAN, RJ9 Headset
- ▶ XML/LDAP, BLF/BLA, Search someone in the Phone book
- ▶ Auto-provision, HTTP/HTTPS/TFTP/FTP,TR069



WS320 Technical Datasheet

► Phone Features

- 2 sip accounts, Hotline
- Call hold, Call waiting, Call forward, Call return
- Call transfer (blind/busy/ask)
- Caller ID display, Redial, Mute, DND
- Auto-answer, 3-way conferencing
- Speed dial, SMS, Voicemail
- Message Waiting Indication LED
- Tone scheme, Volume control
- Direct IP call without SIP proxy
- Ring tone selection/import/delete
- Phonebook (Personal Phone Book search input/output TTL 300 entries)
- Black list
- Hand-free indicator
- One-key back ©
- Call history: dialed/received/missed(50 - entries)
- Configure through User Interface/UI
- Multi-Language
- Wireless
- Programmable Soft Keys, Supports PC control
- Support switching SIP server & Second server

► Advanced Features

- XML Phone Book search and input & output
- Enterprise phone book(800 entries)
- LDAP phone book
- Functions customizable keys

► IP PBX System Integration

- Busy lamp field (BLF), BLF list
- Bridged line appearance (BLA)
- DND & Forward synchronization
- Intercom, Paging, (MoH)
- Call pickup, Dial Plan, Call recording

► Compatible with the platform



- Anonymous call, Anonymous call rejection
- Network conference, Distinctive ringtone

► Security

- LLDP, VLAN QoS (802.1pq),VPN(L2TP)
- Transport Layer Security (TLS)
- Digest authentication using MD5/MD5-session
- Secure configuration file via AES encryption
- Phone lock for personal privacy protection
- Admin/User 2-level configuration mode

► Network Features

- SIP v1 (RFC2543), v2 (RFC3261), DNS SRV (RFC3263)
- Support 802.11b/g, 802.11b/g/n, 802.11g/n
- NAT Traversal: STUN mode
- DTMF: In-Band, RFC2833, SIP Info, Auto
- HTTP/HTTPS Web Management
- IP Assignment: Static/DHCP/PPPoE
- Bridge/Router mode for PC port
- TFTP/DHCP/PPPoE client
- DNS client, NAT/DHCP server
- Ipv4

► Management

- Auto-provision via FTP/TFTP/HTTP/HTTPS
- SNMP V1/2, TR069
- Configuration: browser/phone/auto-provision
- Trace package and system log export

► Codes and Voice Features

- Wideband Codec: G.722
- Narrowband codec: G.711µ/A, G.723.1
- G.726, G.729AB, iLBC
- VAD, CNG, AEC, AGC

- Full-duplex

► Physical Features

- 132x64 graphic LCD
- 49 keys including 12 programmable keys
- 22 LEDs: 1x headset light, 2xaccount lights, 1x message light, 1x headset light, 12xprogrammable lights, 4x function lights, 1x speaker lights,
- Wall-mountable
- 1x RJ-9 handset port
- 1xRJ-9 headset port
- 2x3.5mm PC headset port
- 1xRJ45 10/100M Ethernet ports
- Power adapter: AC 100~240V input and DC 5V/1A output
- Power consumption: 2.5-3.5W
- Net weight: 1.2KG
- Dimension: 287x214x90MM
- Operating humidity: 10~95%
- Storage temperature: up to 60°C

► Package

- PCS/CTN:10PCS
- Carton Meas: 500x480x320MM,
- Measurement:0.068CBM(0.5% more or less)
- N.W/CTN:12.50KGS
- G.W/CTN:13.50KGS

► Certifications

RoHS CE FC 

ES CENE

Communication starts from **SayHi™**

Escene Communication Co.,Ltd

Address: Floor 4 Building C YueAn Industrial Park No.51
Huangcun Road Tianhe District, Guangzhou, China.

Postal Code: 510665

Tel: (+86)20-28096798

Fax: (+86)20-28096786

www.voipon.co.uk sales@voipon.co.uk Tel: +44 (0)1245 808195 Fax: +44 (0)1245 808299