

## BE THE FIRST TOSEE



The 4G standard is the latest technology in intensified night vision. 4G is particularly suitable to address the stringent requirements of special forces operators. Only 4G can offer ultra-fast Auto-Gating, the smallest halo and unrivalled spectral range from ultraviolet to near infrared. Gain the unfair advantage in the darkest nights, in all terrain and operations. Get the best DRI\* range and be the first to see.

## Photonis: leader in design and manufacture of state-of-the-art image intensifier tubes for military applications.

- Best DRI\* range
- Smallest halo
- **Ultra-Fast Auto-Gating**
- Spectral range from 400nm to 1000nm
- Selected by Tier 1 Special Forces
- Also available in 16 mm
- Non-ITAR product
- NATO registered supplier



	Minimum	Typical	Maximum	Unit
FOM (Figure Of Merit)*	1800	2200		
Signal-To-Noise Ratio	28	30		
Limiting resolution	64	72		lp/mm
High Light Level Resolution (200 lx)	55			lp/mm
Ultra Fast Auto-Gating Power Supply Unit				
Response time		0.1	0.2	5
Rise Time Off-to-On		0.5	0.6	S
Input current		25	30	mA
Other Technical Data				
Phosphor	P43 (also available in P45**)			
Operational life time	10.000			hours
Halo (with 0.35mm input spot)		0.75		mm
Gain at 2 x 10 <sup>-5</sup> lx	10.000		20.000	cd/m²/lx
(Gain at 2 x 10 <sup>-6</sup> fc)	(31.000)		(63.000)	fL/fc
Max. Output Brightness	4		17	cd/ m <sup>2</sup>
(Max. Output Brightness)	(1,2)		(4,9)	fL
E.B.I.		0.15	0.25	μlx
Weight (16mm)		45	50	g
Weight (18mm, anvis)		70	75	g
Shock resistance	500			g's



\*\* P45 is Onyx (white phosphor)









## Photonis Netherlands B.V. Photonis France S.A.S.

Dwazziewegen 2 Avenue Roger Roncier 9301 ZR Roden 19100 Brive La Gaillarde The Netherlands +31 (0)505 01 88 08 T +33 (0)555 86 37 00 +31 (0)505 0114 56 F +33 (0)555 86 37 74 E nightvision@photonis.com E nightvision@photonis.com W www.photonis.com W www.photonis.com

NCAGE: H6523 NCAGE: F2245

## www.photonis.com

Photonis Technologies S.A.S. The information furnished is believed to be accurate and reliable, but is not guaranteed and is subject to change without notice. No liability is assumed by Photonis for its use. Performance data represents typical characteristics as individual product performance may vary. Customers should verify that they have the most current Photonis product information before placing orders. No claims or warranties are made as to the application of Photonis products. Pictures may not be considered as contractually binding. This document may not be reproduced, in whole or in part, without the prior written consent of Photonis. Photonis 4G products are not subject to US ITAR control. However, they may require export approval as per applicable regulation depending on the end-user country and specification.

<sup>\*</sup>DRI= Detection, Recognition and Identification