

# ES CENE

# HD

## Three Lines WIFI IP Phone

### WS282-P



## 5.8G WiFi

Escene WS282-P is a highly innovative based wireless SIP VoIP phone, It can perfectly satisfy with all kinds of the businessman communication. WS282-P integrates with 2.4" 132x64-pixel graphical LCD with backlight, a large resolution display screen, elegant and intuitive user interface, which indicate you can enjoy perfect user experience. WS282-P offers high audio quality HD handset, HD speaker and HD codec (G.722), with a rich set of business communication features that can definitely improve working efficiency and sense. Escene WS282-P is highly suitable for SMEs, Home Office and ISP applications.

WS282-P wifi IP phone, help user connect the network simply and enjoy the network easily.

## Key Features

- Wireless working frequency 5.8GHz.
- 2.4" 132\*64-pixel Graphical LCD with backlight.
- HD Voice: HD Codec, HD Speaker, HD Handset.
- Multi-language: Chinese, English, French, Russian, etc.
- One standard (42.5° ) level bracket and wall-mountable.
- 3 SIP accounts and support three-way conference, SMS.
- 2xLAN, PoE(option), 1xRJ9Headset.
- XML/LDA, Contact Search.
- Auto-provision, HTTP/TFTP/FTP.
- Support 15 paperless programmable keys.

# WS282 Technical Datasheet

## Phone Features

3 SIP accounts, Hotline  
Call hold, Call waiting, Call forward, Call return  
Call transfer (blind/busy/ask)  
Caller ID display, Redial, Mute, DND  
Auto-answer, 3-way conferencing  
Speed dial, SMS, Voicemail  
Message Waiting Indication LED  
Tone scheme, Volume control  
Direct IP call without SIP proxy  
Ring tone selection/import/delete  
Phonebook (local up to 1000 entries)  
Black list, Hand-free indicator.  
Call history: dialed/received/missed (100  
-entries); One-key back (C)  
Multi-Language (2aB/abc/ABC/123)  
Soft keys programmable, Supports PC control  
Support switching SIP server & Second server

## Advanced Features

XML Phone Book search and input & output  
Enterprise phone book(800 entries)  
LDAP phone book  
Auton URL & Active URI  
Functions customizable keys  
XML Browser

## IP PBX System Integration

Busy lamp field (BLF), BLF list  
Bridged line appearance (BLA)  
DND & Forward synchronization  
Intercom, Paging, Music on hold  
Call pickup, Dial Plan, Call recording

## Compatible with the platform



## Codes and Voice Features

Wideband Codec: G.722  
Narrowband codec: G.711μ/A, G.723.1  
G.726, G.729AB,iLBC  
VAD, CNG, AEC, AGC, Full-duplex,

## Security

VLAN QoS (802.1pq)  
Phone lock for personal privacy protection  
Admin/User 2-level configuration mode , LLDP, CDP  
L2TP VPN tunneling protocol - added

## Network Features

SIP v1 (RFC2543), v2 (RFC3261)  
SIP connection: Proxy mode & Peering Points mode;  
DNS SRV (RFC3263);  
Redundant server support  
NAT Traversal: STUN mode  
DTMF: In-Band, RFC2833, SIP Info, Auto  
HTTP/HTTPS Web Management  
IP Assignment: Static/DHCP/PPPoE  
Bridge/Router mode for PC port  
TFTP/DHCP/PPPoE client  
DNS client, NAT/DHCP server  
Layer 3 ToS, DSCP

## Management

Auto-provision via FTP/TFTP/HTTP/HTTPS  
Configuration: browser/phone/auto-provision  
Trace package and system log export

## Physical Features

2.4"132x64 graphic LCD; 34 keys including 2  
programmable keys; 1xRJ9 headset port;  
2xRJ45 10/100M Ethernet ports;  
WIFI 5.8GHz  
Line keys with LED indicator: 3  
LED for call and message waiting indication;  
Dual-color (red or green) illuminated LEDs for  
line status information;  
42.5° bracket and wall-mountable  
Power adapter: AC 100~240V input and  
DC 5V/1A output;  
Power over Ethernet ,IEEE 802.3af,class 0  
Power consumption: 1.4-2.6W  
Net weight:  
Dimension:  
Operating humidity: 10~95%  
Storage temperature: up to 60°C

## Package Features

Qty/CTN: 10 PCS  
N.W/CTN:  
G.W/CTN:  
Measurement:  
Carton Meas:

## Certifications



**ES CENE**

Communication starts from **SayHi™**

**ESCENE COMMUNICATION CO.,LTD**

Add: Floor 4 building C YueAn Industrial Park No.51 Huangcun Road Tianhe District,Guangzhou,China.

Tel: (86)20-82320720 Fax: (86)20-82326757