Model



Detector Resolution	384×288
Pixel Size	12μm
NETD	≤40mk
Frame Rate	50Hz
Objective Lens	25mm
Field of View	10.51 × 7.89
Magnification	1-4×
Detection Range(Target size:1.7m×0.5m, P(n)=99%)	1299m
Display Resolution	2.69" OLED
Battery	One replaceable 18500 battery
Max. Battery Life	5h
Weight(without batteries-18500)	<500g
Dimension	66mm×90mm×88mm
Interface	Type-C
Storage, G	32



IRay Technology Co., Ltd.

Tel: 400-998-3088 Fax: +86-535-3410604
Mail: infirayoutdoor@infiray.com Web: www.infirayoutdoor.com
Add: 11th Guiyang Street, YEDA, Yantai 264006, P.R.China





Holo HL 25

Holo HL25 is a large-screen direct-vision thermal imaging scope. You can use it to capture or aim at targets with your eyes. Holo HL25 makes upgrades and improvements on the basis of the first generation, it can be used in hunting, searching, aiming, high-end war game, family defense, and other scenarios.





-\(\) '- Upgraded 2.69"AMOLED Display

The HOLO series is equipped with a 2.69-inch ultra-clear AMLOLED display which provide a much bigger view making it easier to detect.





High-performance Detector

The HOLO Series adopts self-developed high-performance 12 µm 384×288 sensor providing crisp HD images.

- Ultra-clear Image Process Mode

The HOLO series uses software to adjust from the original large HD screen to make the image clearer and bring you a better visual experience.





Laser Rangefinder

LRF is able to achieve facilitate confirmation of prey distance and provide position reference for hunting with an accuracy of ± 1 m and a maximum distance of 1000 m.



The HOLO series is equipped with a unique quick removal clip for quick hand installation and disassembly from the Picatini guide rail.



-\rightarrow-PIP

The screen of cursor position is magnified twice to highlight the target and assist in observing the target details



32GB Built-in Memory

The 32GB memory of HOLO Series makes it possible to record all night, meeting the requirements of whole-hunting process recording.

Upgraded Waterproofing

External screen can prevent water flowing into the interface under rainy scenarios.





32GB







Photo