

PFI-A625P Thermal Monocular Camera



Key Features

- Vanadium oxide uncooled focal plane detector.
- Rugged Mg housing.
- FHD OLED display.
- Replaceable 18650 battery.
- High optical magnification.
- Left and right hand user friendly design.
- Built-in EMMC (32 GB).
- Lightweight and portable.
- IP67 rated.

Technical Specification

Thermal	
Detector Type	Vanadium oxide uncooled focal plane detector
Effective Pixels	640 (H) × 512 (V)
Pixel Pitch	12 μm
Spectral Range	8 μm–14 μm
Sensitivity (NETD)	≤20 mK@f/1.0, 25 °C
Focal Length	25 mm
Aperture	F1.0
Field of View	H: 17.5°; V: 14.0°/H: 30.7 m; V: 24.6 m (@100 m)
Focus Control	Manual
Close Focus Distance	2 m (6.56 ft)
Detection Distance	1,300 m (4,265.09 ft)
Recognition Distance	800 m (2,624.67 ft)
Identification Distance	500 m (1,640.42 ft)
Magnification	1.68 ×
Frame Rate	50 Hz
Display	
Screen	1440 × 1080, OLED
Color Palettes	6 (white hot/black hot/iron red/alarm/emerald/amber)
Video Compression	H.264
Diopter	−3 D to +5 D
Eye Relief	15 mm (0.59 inch)
Exit Pupil	8 mm (0.31 inch)
Function	
Digital Zoom	1×, 2×, 4×, 8×
Video Recorder	Yes
Snapshot	Yes
Wi-Fi Hotspot	Yes
Hot Spot Track	Yes
Video Distance Measurement	Yes
FFC Calibration	Auto, Manual, External Correction
Standby Mode	Yes
DPC (Defective Pixel Correction)	Yes
Storage	Built-in EMMC (32 GB)

Power	
Battery Type	Replaceable 18650 battery
Battery Life	6 h@25 °C (Wi-Fi off)
Power Supply	5 VDC/2 A
Port	USB Type-C
Overvoltage Protection	Yes
General	
Operating Temperature	−30 °C to +55 °C (−22 °F to +131 °F)
Operating Humidity	≤95%
Protection Grade	IP67
Packaging Dimensions	228 mm × 120 mm × 187 mm (8.98" × 4.72" × 7.36") (L × W × H)
Product Dimensions	168 mm × 50 mm × 78 mm (6.61" × 1.97" × 3.07") (L × W × H)
Gross Weight	≤1.6 kg (3.53 lb)
Net Weight	≤355 g (0.78 lb) (battery excluded)

Dimensions (mm[inch])

