

TwistPort™ Adaptor for Rocket AC

ADAPTOR FOR ROCKET™ 5AC-LITE

The TwistPort™ Adaptor for Rocket AC makes the Rocket™ 5AC Lite compatible with all TwistPort™ Antennas. TwistPort™ Adaptors have our proprietary quick-locking waveguide connector, enabling simple connection and detachment of Rocket™ 5AC-Lite without any tools. TPA-R5AC features upgrades in the form of improved feed elements.



TECHNICAL DATA

Antenna Connection	TwistPort™ - Quick Locking Waveguide Port
Radio Connection	2x Slide-On RP-SMA
Materials	Insert - Aluminium Alloy Adaptor - UV stabilized and weather resistant ABS plastic
Flame Rating	UL 94 HB
Temperature	-40°C to +60°C (-40°F to +140°F)
Wind Survival	160 km/h
Weight	0.4 Kg / 0.9 lbs – single unit 0.5 Kg / 1.1 lbs – single unit incl. package 11.5 Kg / 25 lbs – carton (20 units)
Single Unit	Retail Box: 13.5 × 13.0 × 11.5 cm
20 Units	Carton Box: 60.5 × 29.0 × 28.5 cm

PERFORMANCE

Frequency Range	5180 - 6400 MHz
Polarization	Dual Linear H + V
VSWR Max	1.8
Impedance	50 Ohm

COMPATIBLE WIRELESS PLATFORMS

RF elements®	any TwistPort™ Antenna
Ubiquiti Networks®	Rocket™ 5AC-Lite

PACKAGE CONTENTS

TwistPort™ Adaptor

PRODUCT DIMENSIONS

