

Thermal Tube Scope Ares660 2.0 Technical Specifications

ThermTec Technology Co., Ltd. Email: info@thermeyetec.com Website: https://www.thermeyetec.com











# Ares660 2.0

#### **Key Features**

- 640\*512 thermal resolution, NETD≤20mK;
- 20/60mm Lens, Dual Field of View;
- 5 colors and 7 reticle choices for reticle options;
- Freeze and zoom of zeroing improve shooting accuracy.;
- Automatic object detection and distance measurement;
- Self-learning image calibration;
- Ultra-long battery life reaches to 16hrs;
- 5 zeroing profiles meet various needs;
- RAV function allows recording every terrific shot;
- Rotary knob design;

### Applications

- Night hunting
- Observation

## Specifications

| Model           | ARES660 2.0                      |
|-----------------|----------------------------------|
|                 | Microbolometer                   |
| Туре            | Uncooled                         |
| Resolution      | 640x512                          |
| Pixel pitch     | 12µm                             |
| NETD            | ≤20mK                            |
| Spectral range  | 8-14µm                           |
| Frame rate      | 50HZ                             |
| Detection Range | 1000/3000m                       |
|                 | Optics                           |
| Objective lens  | 20/60mm, F1.0                    |
| Field of view   | 21.7°x17.4°/ 7.3°x5.9°           |
| m@100m          | 38.4x30.7/12.8x10.2              |
| Magnification   | 1.1X/3.2X                        |
| Digital zoom    | 1.0-4.0X smooth & rapid zoom     |
| Eye relief      | 50mm                             |
| Exit pupil      | 6mm                              |
| Diopter         | ±5D                              |
|                 | Aiming Reticle                   |
| Reticle         | 7                                |
| Reticle color   | 5,Black. white, red, green, blue |
|                 | Display                          |
| Туре            | AMOLED                           |
| Resolution      | 1024x768                         |
| Display size    | 0.39 inch                        |
| Color palette   | 6                                |

| Function                              |  |  |
|---------------------------------------|--|--|
| Max. recoil power on rifled<br>weapon | 6000J  |  |
| Mounting brackets on weapon           | Standard 30mm rings  |  |
| RAV                                   | Yes  |  |
| Audio Recording                       | Yes  |  |
| Auto zeroing                          | Yes  |  |
| Manual zeroing                        | Yes  |  |
| Zeroing profiles                      | 5  |  |
| Freeze Zeroing                        | Yes  |  |
| Picture-in-picture                    | Yes  |  |
| Al ranging                            | Yes  |  |
| Image calibration                     | Manual/Auto  |  |
|                                       | Video Recorder   |  |
| Phone/video playback                  | Yes  |  |
| Inbuilt memory                        | 64GB   |  |
| Interface                             |  |  |
| Туре С                                | Data transfer  |  |
| Hotspot                               | Yes  |  |
| Battery                               |  |  |
| Battery type                          | Replaceable, 1*18650 or 18500<br>battery,1*18650 inbuilt battery |  |
| Battery reverse connection            | Yes  |  |
| Battery life                          | 16h  |  |
|                                       | Environment  |  |
| Operating temperature                 | -20- +50°C   |  |
| IP rating                             | IP67   |  |
| Weight, g                             | 1072   |  |
| Size, mm                              | 435.7*89.5*92.9  |  |
|                                       | Accessories  |  |
| External cable                        | USB data cable   |  |
| Other accessory                       | 2x standard 30mm rings, eyeshade and etc.                        |  |

### Accessories



## Dimension

#### Unit: mm

