# UNIVOIS

#### Office IP Phone



## **U1**

- 2.4" 128x64-pixel HD display with backlight;
- 3 multi-functional line keys, up to 15 Paperless DSS Keys;
- Optima HD voice, Full-duplex speakerphone;
- Dual-port 10/100M Ethernet, integrated POE;
- 1xBuilt-in USB Port;
- Up to 3 SIP accounts, 3-way conferencing;
- Wall-mountable, integrated stand with 2 adjustable angles;









## Office IP Phone U1

Anonymous call rejection

>Network conference, Distinctive ringtone

### The Perfect IP Phone For Office

Phone Features	Codes and Voice Features	Physical Features
>3 SIP accounts, Hotline	>Wideband Codec: G.722	>128x64-pixel display with blacklight
>Call hold, Call waiting, Call forward, Call return	>Narrowband codec: G.711μ/A,	>34 keys, 5LED lights,
>Call transfer (blind/busy/ask)	G.726, G.729AB,iLBC	>Wall-mountable
>Caller ID display, Redial, Mute, DND	>VAD, CNG, AEC, AGC	>1xRJ-9 handset port
>Auto-answer, 3-way conferencing	>Full-duplex,	>1xRJ-9 headset port
>Speed dial, SMS, Voicemail Message Waiting		>2xRJ45 10/100M Ethernet ports
Indication LED	Security	>Power adapter: AC 100~240V input and
>Tone scheme, Volume control	>LLDP, VLAN QoS (802.1pq),VPN(L2TP)	DC 12V/1A output
>Direct IP call without SIP proxy	>Transport Layer Security (TLS)	>1x USB port
>Ring tone selection/import/delete	>Digest authentication using MD5/MD5-sess	>Power over Ethernet ,IEEE 802.3af,class 0
>Black list, Hand-free indicator.	>Secure configuration file via AES encryption	>Power consumption: 2.5-3.5W
>Call history: dialed/received/missed;	>Phone lock for personal privacy protection	>Net weight:
>Multi-Language	>Admin/User 2-level configuration mode	>Dimension:
>Soft keys programmable, Supports PC control		>Operating humidity: 10~95%
	Network Features	>Storage temperature: up to 60°C
Advanced Features	>SIP v1 (RFC2543), v2 (RFC3261)	
>XML Phone Book search and input & output	>DNS SRV (RFC3263)	Package Features
>Enterprise phone book 800	>NAT Traversal: STUN mode	>Qty/CTN: 10 PCS
>LDAP phone book 300	>DTMF: In-Band, RFC2833, SIP Info, Auto	>N.W/CTN:
>Functions customizable keys	>HTTP Web Management	>G.W/CTN:
>Support up to 15 paperless DSS keys	>HTTPS Web Management is optional	>Carton Meas:
>Support EHS	>IP Assignment: Static/DHCP/PPPoE	
	Bridge/Router mode for PC port	Certifications
IP PBX System Integration	>TFTP/DHCP/PPPoE client	11107
>Busy lamp field (BLF), BLF list	>DNS client, NAT/DHCP server	RoHS (( FC
>Bridged line appearance (BLA)		NON3 (( I @ Sages
>DND & Forward synchronization	Management	
>Intercom, Paging, Music on hold	>Auto-provision via FTP/TFTP/HTTP/HTTPS	
>Call pickup, Dial Plan, Call recording Anonymous call,	>SNMP V1/2 , TR069 is optional	

>IPv6 is optional

>Configuration: browser/phone/auto-provision

>Trace package and system log export

