CooVox-C4000

Enterprise-Grade IPPBX System



Product Datasheet

The CooVox–C4000 is a high–end, heavy–duty and yet cost–effective enterprise–grade IPPBX system for the large enterprises. It is a fully featured IPPBX system with high system capacity, allowing the CooVox–C4000 to fulfill a business's existing telecommunication needs while also providing future growth options and all of this without additional license fees.

CooVox–C4000 is ideal for those enterprises which have a demanding telephony environment, as it supports up to 4000 extensions, 600 simultaneous calls, 600 simultaneous conference attendees, up to 60000 hours call recording. All features are available to use with no additional license fees.

Features

Quick Setup Wizard

Quick Setup Wizard allows speedy initial configuration of the C4000 system. The wizard includes all essential configuration steps in an easy to use and intuitive web based interface.

Endpoints Provisioning

Quick and simple deployment of endpoint devices using PNP and Quick Register Code. CooCall APP can be provisioned by scanning a QR code.

Expansion Box Provisioning

Combining CooVox series IPPBX with EX16S Gateways can result in deployment time savings of 90% when deploying large amounts of analog phones.

Email Notifications

SMTP templates allow for simple configuration of mail server. Fax to email, voicemail to email, send QR code via email, system events email notifications, etc.

One Number Stations

The same extension can now be registered on 5 different endpoints. This means that a desktop IP phone and mobile phone APP can share the same extension number so wherever you are, you'll never miss any important calls.

Extension Web Portal (WebRTC Integrated)

Thanks to the extension web portal, you can now Playback voicemail/recordings online, make/receive phone calls, click to dial, incoming call pop–up, send fax. All of this from within your web browser without installing any plugins.

CooVox-C4000

Product Datasheet

Enterprise-Grade IPPBX System

Specifications

Hardware	Specifications
CPU	Intel quad-core
RAM	8GB DDR4
Storage	4TB + 4TB RAID1
USB (Extended Storage)	6 x USB2.0
Ethernet Interface	2 (WAN/LAN)
Power	180~260V/47~63Hz ≤ 4A(450W 1+1 RPS)
Size	1U industry standard rack-mountable chassis

Software	Specifications	
System Capacity	1000 Extensions400 Simultaneous Calls	 400 Conference Attendees 60000hrs Recording/Voicemail (Internal Storage)
Protocols & Codecs	 SIP(RFC3261), IAX2 DTMF(RFC4733, SIPINFO, In–Band) Transport Protocols: UDP, TCP, TLS, SRTP 	 Video Codecs: VP8, H.264, H.263+, H.263, H.261 Audio Codecs: Opus, G.722, G.711(a-law, u-law), G.729, G.726, GSM, SPEEX
Feature Highlights	 Quick Installation Guide Softphone APP Auto Provisioning (Scan QR Code) IP Phone Auto Provisioning (PNP, Quick Register Code) LDAP Phonebook Auto Configure (H81, H83) 	Fax to EmailVirtual FaxClick to Dial (WebRTC)
Telephony Features	 Call Queue Ring Group Caller ID Call Forward Call Forward Call Transfer Call Pickup Call Parking Call Waiting IVR (Multi–layer) Caller ID Call Spy Call Spy Video Call S-way Calling Conference Call Follow Me 	 DISA Smart DID Blacklist Voicemail Wakeup Call PIN Code Do Not Disturb Time Conditions Paging & Intercom One Number Stations Music On Ringback Distinctive Ringtone Auto Call Recording One Touch Recording
Multi-level User Administration	 Admin user: All Privileges. Operator user: Manage extensions, general features, faxes, CDR, call recordings, etc. 	 Extension user: WebRTC, extension recording, extension voicemail, extension call logs, etc
Security	 Firewall based on iptables Geo–IP (Security policy based on IP address geographical location) 	 Intrusion auto detection and prevention
Network Features	 Network Mode (WAN): Static IP, DHCP VPN: PPTP (Server and Client), OpenVPN (Server and Client) 	DHCP (Server and Client)